





















		Size / mm	Diameter ø	Size / mm	Diameter ø	ROLLS	
1		Angle leg out Köşebent dışı	50x50x5 100x100x10 120x120x15	650 1100 1300	50x50x6 90x90x8 100x100x10	700 1000 1400	AE F F
2		Angle leg in Köşebent içi	50x50x5 80x80x8 120x120x15	650 900 1300	50x50x6 80x80x8 100x100x10	800 1200 1600	AE
3		T section leg out T profil Dışa	120	1200	100	1200	A
4		T section leg in T profil içi	100	1200	100	1000	A
5		T section leg side T profil yana	130	1300	120	1200	A
6		Plate hard way Lama zoruna	40x10 125x25 140x30	500 850 3000	40x10 100x20 120x25	400 600 1600	AF
7		Plate easy way Lama kolayına	200x50	1000	60x10 100x40 200x35	400 600 1000	AF
8		Square / Kare	75x75	800	30 50 60	400 500 1000	AF
9		Round / Yuvarlak	Ø85	900	40 60 70	400 600 800	B
10		Tube / Boru	Ø50x2 Ø160x4	600 3000	50x2 120x2 140x3	600 2000 3000	B
11		Tube-pipe/ Boru	101.6x12 139.7x5	1200 1600	60.3x3.2 114.3x3.6 114.3x4.5	400 1000 1600	B
12		Rectangle tube Dikdörtgen Profil	140x50x5	500 3000 4000	40x20x2 100x50x5 140x40x3	500 3000 4000	B
13		Square tube Kare Profil	90x90x8	500 2500 3000	50x50x2.5 90x90x4 100x100x5	500 2500 3000	B
14		Channel easy way- legs out U profil kolayına-dışa	UNP200	1000	UNP180 UNP180	800 1200	AD F
15		Channel easy way- legs in U profil kolayına-içe	UNP200	1200	UNP80 UNP180	800 1200	AD F
16		Channel hard way C profil zoruna	UNP100	8000			CB
17		Beam easy way / Kiriş kolayına	UNP200	1200	INP90 INP180	600 800	AD F
18		Beam easy way / Kiriş kolayına	HEA140 HEB120	1200 1300	HEA120 HEB100	1000 1200	AD F
19		Beam hard way Kiriş Zoruna	INP140	6000			CB
20		Beam hard way Kiriş Zoruna	HEA120 HEB100	2600 1500			CB
Max. Section Modulus cm³ Maks. Dayanım Momenti			120		80		
Power / Motor Gücü kW			15		11		
Rolls ø / Vals Topları ø mm			390		315		
Shaft ø / Mill ø mm			120		100		
Bending Speed / Bükme Hızı			6 m ³ /min.		5.4 m ³ /min.		
Weight / Ağırlık kg			4720		2240		
WXLXH / GxLxY mm			1450x1985x2040		1500x1650x2100		