



















		Size / mm	Diameter ø	Size / mm	Diameter ø	ROLLS	
1		Angle leg out Köşebent dışa	160x20	1600	150x15	1000	AD
2		Angle leg in Köşebent içe	150x20	1600	130x15	1200	AD
3		T section leg out T profil dışa	160x20	1400	150x15	1200	AD
4		T section leg in T profil içe	150x20	2000	130x15	1700	AD
5		T section leg side T profil yana	160x20	1500	150x15	1300	AD
6		Plate hard way Lama zoruna	175x40	1300	150x35	1000	A
7		Plate easy way Lama kolayına	350x50	900	250x40	1000	A
8		Square / Kare	110x110	1500	90x90	1400	A
9		Round / Yuvarlak	Ø130	1600	Ø100	1000	B
10		Tube / Boru	Ø219,1x8x18	2500	Ø168,3x71	2500	B
11		Square tube Kare Profil	150x150		120x120		B
12		Channel easy way-legs out U profil kolayına-dışa	UNP 360	1200	UNP300	1100	B
13		Channel easy way-legs in U profil kolayına-içe	UNP 360	1400	UNP300	1100	B
14		Channel hard way C profil zoruna	UNP 200	11000	UNP160	10000	BC
15		Beam easy way / Kiriş kolayına	INP 360	1500	INP300	1200	B
16		Beam easy way / Kiriş kolayına	HEA 240 HEB 200	1500 1500	HEA 180 HEB 160	1100 1100	B
17		Beam hard way Kiriş Zoruna	IPE 200	5000	IPE 160	3500	BC
18		Beam hard way Kiriş Zoruna	HEA 180 HEB 160	4500 3200	HEA 120 HEB 120	3500 2800	BC
Max. Section Modulus cm³ Maks. Dayanım Momenti			320		210		
Power / Motor Gücü kW			30		15		
Rolls ø / Vais Topları ø mm			550		460		
Shaft ø / Mill ø mm			240/220		180/160		
Bending Speed / Bükme Hızı			0-7 m/min.		0-7 m/min.		
Weight / Ağırlık kg			17500		9250		
WXLxH / GxÜxY mm.			2240x3360x2055		2000x2400x695		