
















TECHNICAL INFORMATION /
TEKNIK ÖZELLİKLER

PRO 50

PRO 40

PRO 30

	Size / mm	Diameter ø	Rolls	Size / mm	Diameter ø	Rolls	Size / mm	Diameter ø	Rolls
1 	50x5 25x3	600 350	A,E	50x5	850	A,E	40x5	400	A,E
2 	45x5 25x3	600 400	A,E	50x5	1200	A,E	40x5	500	A,E
3 	50	600	A	50	650	A	50x6	800	A
4 	50	600	A	50	900	A	50	850	A
5 	50	600	A	50	900	A	50	800	A
6 	60x10 20x10	800 300	A	60x10 50x12	800 800	A	60x10 50x10	500 600	A
7 	80x15	600	A	120x15	750	A	80x15	900	A
8 	32x32	700	A	35x35 35x35	1200 800	A	30x30 20x20	1200 900	A
9 	Ø35	700	B	Ø35	900	B	Ø30	1200	B
10 	Ø60x2 Ø15x1	1000 350	B	Ø70x2	1200	B	Ø60x2	900	B
11 	Ø60,3x2,9 Ø17,2x2	1000 300	B	33,7x2,65	900	B	48,3x2	900	B
12 	60x30x3	-	B	50x40x3	850	B	50x30x3	700	B
13 	45x45x3	-	B	60x60x3	830	B	40x40x3	350	B
14 	UNP80	800	B	UNP60 (60x30x6)	1200	B	UNP50 (50x25x5)	1200	B
15 	UNP80	1200	B	UNP60 (60x30x6)	1200	B	UNP50 (50x25x5)	1200	B
Power / Motor Gücü kW		15 + 075			15		075		
Rolls ø / Vals Topları ø mm		Ø152 Ø162 Ø162			Ø155		Ø137 Ø132 Ø132		
Shaft ø / Mil ø mm		Ø50 Ø40 Ø40			Ø50		Ø35 Ø30 Ø30		
Bending Speed / Bükme Hızı		3,3 m/min.			4,3 m/min.		2,1 m/min.		
Weight / Ağırlık kg		500			400		200		
WXLXH / GxÜxY mm.		1000x950x450			900x1050x400		850x730x1500		

A: Standard rolls B: Special rolls C: Pulling device D: For bending without deformation and for serial production special rolls are required.

A: Standart Vals Topları / B: Özel Vals Topları / C: Çekirge Aparatı / D: Seri Üretim için Özel Vals Topları